



G6 Paste

Rapid Grade Paste Compound

Product Description

G6 Rapid Grade Paste Compound is for use on OEM, Refinish Medium Solids and Air Dried 2k paint systems (well cured).

Technical Information

Appearance: Cream coloured paste
 Viscosity: High viscosity
 VOC Content: 11.2% of total product
 Relative Density: 1.44
 pH: 9.41
 Paint Type Compliance: MS & HS

Product Information

Size	Code	Ctn Qty
400g	G6-400	12
3kg	G6-3000	4

Key Benefits

- | | |
|---------------------|--|
| • Permanent Finish | Removes P1500 abrasive marks quickly and easily with no fillers |
| • Silicone Free | Can be used in bodyshops and applied nearby to where paints are used |
| • High Gloss System | Can be used with G10 Finishing Compound for an enhanced gloss finish |

Use With


Machine Application




G Mop 6" Standard
Compounding Head
SGM-14 (Head -
14mm thread)
SGM-58 (Head -
5/8" thread)



Water Spray
Bottle
WSB



Farécla Finishing
Cloth
FC-3




Farécla Finishing
Cloth
FC-3

How To Use


Machine Application




Soak
compounding
head
SGM-14 (head)




Attach pad to the
polishing machine,
spin off excess
water and knead



Shake bottle or mix
compound well
and apply to pad
or surface
G6-3000 (3kg)



Spread and
compound at
1500 - 1800rpm




Wipe clean with
Finishing Cloth
FC-3 (cloth)


Hand Application




Soak and rinse out
Farécla Finishing
Cloth
FC-3 (cloth)
WSB (water spray
bottle)



Shake bottle or mix
compound well
and apply to cloth
or surface
G6-3000 (3kg)



Rub product on
the surface in a
back and forth
motion



Wipe clean with
Finishing Cloth
FC-3 (cloth)

*It is always recommended to test on an inconspicuous area prior to general use