

# WEST SYSTEM® 404 High-Density Filler

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 03/16/2016

Revision date: 01/25/2019

Version: 404-2019a

### SECTION 1: Identification

#### Identification

**Product name** : WEST SYSTEM® 404 High-Density Filler

**Product code** : 404, 404-15, 404-45, 404-B

#### Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** : Thickening agent for liquid epoxy resins.

#### Details of the supplier of the safety data sheet

#### Manufacturer

Gougeon Brothers, Inc  
100 Patterson Ave.  
Bay City, MI 48706 - U.S.A.  
T 866-937-8797 or 989-684-7286  
[www.westsystem.com](http://www.westsystem.com)

#### Emergency telephone number

**Emergency number** : CHEMTREC 1 (800) 424-9300  
CHEMTREC International +1 (703) 527-3887 24 hr

### SECTION 2: Hazard(s) identification

#### Classification of the substance or mixture

Not classified.

#### Label elements

No labelling applicable

#### Other hazards

No additional information available

#### Unknown acute toxicity

Not applicable

### SECTION 3: Composition/information on ingredients

#### Substance

Not applicable

#### Mixtures

Name	Product identifier	HPR %
Wollastonite (Ca(SiO <sub>3</sub> ))	(CAS No) 13983-17-0	80 - 100
Dimethyl silicone polymer with silica	(CAS No) 67762-90-7	5 - 10
Limestone	(CAS No) 1317-65-3	0.1 - 1.5
Diopside	(CAS No) 14483-19-3	0.1 - 1.5
Feldspar	(CAS No) 68476-25-5	0.1 - 1.5

The exact chemical identity and/or exact percentage (concentration) of each ingredient may be held as confidential business information (CBI). Any ingredient not disclosed in this section may have been determined not to be hazardous to health or the environment, or it may be present at a level below its disclosure threshold.

### SECTION 4: First aid measures

#### Description of first aid measures

**First-aid measures after inhalation** : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

**First-aid measures after skin contact** : If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists.

**First-aid measures after eye contact** : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.

# WEST SYSTEM® 404 High-Density Filler

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

**First-aid measures after ingestion** : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

### Most important symptoms and effects, both acute and delayed

**Symptoms/injuries after inhalation** : May cause respiratory tract irritation.

**Symptoms/injuries after skin contact** : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

**Symptoms/injuries after eye contact** : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

**Symptoms/injuries after ingestion** : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

### Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

## SECTION 5: Firefighting measures

### Extinguishing media

**Suitable extinguishing media** : Foam. Carbon dioxide. Dry chemical. Water fog. Water spray.

**Unsuitable extinguishing media** : Do not use a heavy water stream.

### Special hazards arising from the substance or mixture

**Fire hazard** : Products of combustion may include, and are not limited to: oxides of carbon.

**Reactivity** : No dangerous reaction known under conditions of normal use.

### Advice for firefighters

**Protection during firefighting** : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**General measures** : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

### For non-emergency personnel

No additional information available

### For emergency responders

No additional information available

### Environmental precautions

No additional information available

### Methods and material for containment and cleaning up

**For containment** : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for cleaning up** : Scoop up material and place in a disposal container.

### Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

## SECTION 7: Handling and storage

### Precautions for safe handling

**Precautions for safe handling** : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.

**Hygiene measures** : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### Conditions for safe storage, including any incompatibilities

**Storage conditions** : Keep out of the reach of children. Keep container tightly closed.

# WEST SYSTEM® 404 High-Density Filler

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 8: Exposure controls/personal protection

#### Control parameters

<b>Wollastonite (Ca(SiO<sub>3</sub>)) (13983-17-0)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica) 3 mg/m <sup>3</sup> (Respirable)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable)
<b>Dimethyl silicone polymer with silica (67762-90-7)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Inhalable fraction) 3 mg/m <sup>3</sup> (Respirable fraction)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup> (Amorphous silica) 15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable)
<b>Limestone (1317-65-3)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Inhalable) 3 mg/m <sup>3</sup> (Respirable)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable)
<b>Diopside (14483-19-3)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Inhalable) 3 mg/m <sup>3</sup> (Respirable)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable)
<b>Feldspar (68476-25-5)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Inhalable) 3 mg/m <sup>3</sup> (Respirable)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (Total dust) 5 mg/m <sup>3</sup> (Respirable)

#### Exposure controls

##### Appropriate engineering controls

: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

##### Hand protection

: Wear suitable gloves.

##### Eye protection

: Safety glasses or goggles are recommended when using product.

##### Skin and body protection

: Wear suitable protective clothing.

##### Respiratory protection

: In case of insufficient ventilation, wear suitable respiratory equipment.

##### Environmental exposure controls

: Maintain levels below Community environmental protection thresholds.

##### Other information

: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

### SECTION 9: Physical and chemical properties

#### Information on basic physical and chemical properties

##### Physical state

: Solid

##### Appearance

: Powder

##### Colour

: Off-white

##### Odour

: Odourless

##### Odour threshold

: No data available

##### pH

: No data available

##### Melting point

: > 1832 °F (1000 °C) Will not freeze

# WEST SYSTEM® 404 High-Density Filler

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Freezing point</b>	: No data available
<b>Boiling point</b>	: No data available
<b>Flash point</b>	: No data available
<b>Relative evaporation rate (butylacetate=1)</b>	: No data available
<b>Flammability (solid, gas)</b>	: Non flammable.
<b>Vapour pressure</b>	: No data available
<b>Relative vapour density at 20 °C</b>	: No data available
<b>Relative density</b>	: 2.45 - 2.96
<b>Solubility</b>	: Slightly soluble
<b>Partition coefficient n-octanol/water</b>	: No data available
<b>Auto-ignition temperature</b>	: No data available
<b>Decomposition temperature</b>	: No data available
<b>Viscosity, kinematic</b>	: No data available
<b>Viscosity, dynamic</b>	: No data available
<b>Explosive limits</b>	: No data available
<b>Explosive properties</b>	: No data available
<b>Oxidising properties</b>	: No data available

### Other information

No additional information available

## SECTION 10: Stability and reactivity

<b>Reactivity</b>	: No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	: Stable under normal storage conditions.
<b>Possibility of hazardous reactions</b>	: No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	: Heat.
<b>Incompatible materials</b>	: None known.
<b>Hazardous decomposition products</b>	: May include, and are not limited to: oxides of carbon.

## SECTION 11: Toxicological information

### Information on toxicological effects

Dimethyl silicone polymer with silica (67762-90-7)	
LD50 oral rat	> 5000 mg/kg OECD 401
LD50 dermal rabbit	> 2000 mg/kg OECD 402

<b>Acute toxicity (oral)</b>	: Not classified.
<b>Acute toxicity (dermal)</b>	: Not classified.
<b>Acute toxicity (inhalation)</b>	: Not classified.
<b>Skin corrosion/irritation</b>	: Not classified.
<b>Serious eye damage/irritation</b>	: Not classified.
<b>Respiratory or skin sensitization</b>	: Not classified.
<b>Germ cell mutagenicity</b>	: Not classified.
<b>Carcinogenicity</b>	: Not classified.

Wollastonite (Ca(SiO3)) (13983-17-0)	
IARC group	3 - Not classifiable

<b>Reproductive toxicity</b>	: Not classified.
<b>STOT-single exposure</b>	: Not classified.
<b>STOT-repeated exposure</b>	: Not classified.
<b>Aspiration hazard</b>	: Not classified.

<b>Symptoms/injuries after inhalation</b>	: May cause respiratory tract irritation.
<b>Symptoms/injuries after skin contact</b>	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

# WEST SYSTEM® 404 High-Density Filler

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Symptoms/injuries after eye contact</b>	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
<b>Symptoms/injuries after ingestion</b>	: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.
<b>Other information</b>	: Likely routes of exposure: ingestion, inhalation, skin and eye.

### SECTION 12: Ecological information

#### Toxicity

**Ecology - general** : May cause long-term adverse effects in the aquatic environment.

#### Persistence and degradability

WEST SYSTEM® 404 High-Density Filler	
Persistence and degradability	Not established.

#### Bioaccumulative potential

WEST SYSTEM® 404 High-Density Filler	
Bioaccumulative potential	Not established.

#### Mobility in soil

WEST SYSTEM® 404 High-Density Filler	
Ecology - soil	No additional information available.

#### Other adverse effects

**Effect on the global warming** : No known effects from this product.

Name	Product identifier	Ecotoxicity Classification Information
Wollastonite (Ca(SiO <sub>3</sub> ))	(CAS No) 13983-17-0	No data available.
Dimethyl silicone polymer with silica	(CAS No) 67762-90-7	No data available.
Limestone	(CAS No) 1317-65-3	No data available.
Diopside	(CAS No) 14483-19-3	No data available.
Feldspar	(CAS No) 68476-25-5	No data available.

### SECTION 13: Disposal considerations

#### Waste treatment methods

**Product/Packaging disposal recommendations** : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

### SECTION 14: Transport information

#### Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT and TDG

Not regulated

#### Transport by sea

In accordance with IMDG

Not regulated

#### Transport by air

In accordance with IATA

Not regulated

### SECTION 15: Regulatory information

#### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories

# WEST SYSTEM® 404 High-Density Filler

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Dimethyl silicone polymer with silica (67762-90-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e., Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).

### 15.2. International regulations

No additional information available

### 15.3. US State regulations


California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

<b>Limestone (1317-65-3)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

**Date of issue** : 03/16/2016  
**Revision date** : 01/25/2019  
**Version** : 404-2019a  
**Other information** : None.

**NFPA health hazard** : 0  
**NFPA fire hazard** : 0  
**NFPA reactivity** : 0



HMIS III Rating

**Health** : 1  
**Flammability** : 0  
**Physical** : 0

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*