

BÜFA®-Accelerator Co 1 /NEW

Cobalt-Accelerator

Prod. No. 7951062

Product description	BÜFA®-Accelerator Co 1 /NEW is a polymerisation accelerator on a cobaltsalt base dissolved in styrene and xylene that is used for curing unsaturated polyester and vinyl ester resins.			
Applications	BÜFA®-Accelerator Co 1 /NEW is used for curing UP and VE resins in conjunction with ketone peroxides at room temperature or moderately increased temperatures.			
Specifications / technical data	Property	Test method	Value	Unit
	Density at 20 °C	DIN 53 217/2	approx. 0.91	g/ml
	Flow-viscosity at 23 °C in an ISO-cup 6 mm	EN ISO 2431	5	s
	Flashpoint	EN ISO 13736:2013	28.5	°C
Directions for use	Shake or stir the contents of the container well before removing accelerator since components may form deposits after longer standing times.			
Note:	Always mix the accelerator with the resin thoroughly first before adding the peroxide!			
Storage/Handling	This product must be stored cool in closed containers, protected from sunlight. Shelf-life is at least 3 months in unopened, original containers stored up to a temperature of 20 °C. Gel and curing times may change with increasing duration of storage.			
	Never mix the accelerator directly with peroxide since this may lead to explosive decomposition of the peroxide!			

Note: The Information given above is based on our current state of knowledge and experience. In view of the many factors that may influence working conditions and the application of our products, the user is not relieved from carrying out his own tests and experiments. No legally binding warranty of certain properties or suitability for a particular purpose can be derived from this information. It is the responsibility of the receiver or user of our products to observe proprietary rights as well as existing laws and regulations. The latest version of the corresponding EU Safety Data Sheet must also be observed.

BÜFA®-Accelerator Co 1 /NEW

Cobalt-Accelerator

Prod. No. 7951062

BÜFA Composite Systems GmbH & Co. KG
Hohe Looge 2-8
26180 Rastede
GERMANY
Phone +49 4402 975-0
Fax +49 4402 975-300
compositesystems@buefa.de
www.buefa.de
www.buefacompositesystems.com

A member of the BÜFA-Group