



## SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Do not use in confined spaces without adequate ventilation and/or respirator.

### STORAGE PRECAUTIONS

Keep containers tightly closed. Keep in original container. Keep away from food, drink and animal feeding stuffs. Keep away from heat, sparks and open flame.

### STORAGE CLASS

Flammable liquid storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
PROPAN-2-OL	WEL	400 ppm	999 mg/m <sup>3</sup>	500 ppm	1250 mg/m <sup>3</sup>	

WEL = Workplace Exposure Limit.

### PROTECTIVE EQUIPMENT



### ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

### RESPIRATORY EQUIPMENT

Wear suitable respiratory protection.

### HAND PROTECTION

Wear protective gloves.

### EYE PROTECTION

Wear approved safety goggles.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

### HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes wet. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Blue Clear		
ODOUR	Characteristic Odour of alcohol		
BOILING POINT (°C)	82°C	RELATIVE DENSITY	0.94-0.96
VAPOUR DENSITY (air=1)	2.1	VISCOSITY	FORD CUP 4 35-40 s 20°C
FLASH POINT (°C)	22°C		

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions and recommended use.

### CONDITIONS TO AVOID

Avoid contact with strong oxidisers. Avoid heat, flames and other sources of ignition.

### HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

Harmful by inhalation.

## INGESTION

May cause internal injury.

## SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

## EYE CONTACT

Irritating to eyes.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

## 13 DISPOSAL CONSIDERATIONS

### GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

## 14 TRANSPORT INFORMATION



UK ROAD CLASS	3		
PROPER SHIPPING NAME	PAINT OR PAINT RELATED MATERIAL		
UN NO. ROAD	1263	UK ROAD PACK GR.	II
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II	ADR LABEL NO.	3
HAZCHEM CODE	3YE	RID CLASS NO.	3
UN NO. SEA	1263	IMDG CLASS	3
IMDG PACK GR.	II	EMS	3-05
MFAG	310, 313	MARINE POLLUTANT	No.
UN NO. AIR	1263	AIR CLASS	3
AIR PACK GR.	II		

## 15 REGULATORY INFORMATION

### LABELLING



Irritant



Highly Flammable

### RISK PHRASES

R11	Highly flammable.
R36	Irritating to eyes.
R67	Vapours may cause drowsiness and dizziness.

### SAFETY PHRASES

S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S51	Use only in well-ventilated areas.
S60	This material and its container must be disposed of as hazardous waste.

