

SAFETY DATA SHEET

According to EC Directive 1907/2006/EC, Article 31

Revision Date: 08/September/2011

Cabot Corporation

157 Concord Road

Billerica, MA 01821

Tel: 1-978-663-3455 Fax: 1-978-670-6955

UNITED STATES

Product Code: M5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE **COMPANY/UNDERTAKING**

Product Name: CAB-O-SIL® Untreated Fumed Silica

Silicon Dioxide, Synthetic Amorphous Silica, Pyrogenic (Fumed) Amorphous Silica Synonyms:

REACH Registration Number: 01-2119379499-16

This SDS is valid for CAB-O-SIL® Fumed Silica, L-50, L-60, L-90, LM-130, LM-150, M-5, M-5K, PTG, MSthe following grades: 55, H-5, H-7D, HS-5, EH-5, LM-130D, LM-150D, M-7D, MS-75D, S-17D, HP-60, M-

8D, EL-1000, EL-2000, MS-35, H300

Rheological control, Flow agent, Reinforcing agent in: Coatings, Adhesives, Various Use of the

Cabot Corporation

UNITED STATES

Tel: 1-217-253-3370

Fax: 1-217-253-5586

700 E U.S. Highway 36

Tuscola, IL 61953-9643

Substance/Preparation:

Supplier:

Cabot GmbH Cabot Carbon, Ltd. Kronenstrasse 2 Sully Moors Road 79618 Rheinfelden Sully, Vale of Glamorgan

CF64 5RP **GERMANY**

Tel: (+49) 7623.7070 Wales, UNITED KINGDOM Fax: (+49) 7623.707 530 Tel: (+44) 1446.736999

Fax: (+44) 1446.737123

Cabot Bluestar Ltd.

Xinghuo Industrial Garden **Cabot Corporation**

Yongxiu County, 3603 South Saginaw Road

Jiujiang City 330319 Midland, MI 48640 Jiangxi Province, CHINA **UNITED STATES** Tel: (86-792) 3170163 Tel: 1-989-495-0030

Fax: (86-792) 3170122 Fax: 1-989-495-2139

E-Mail Address: SDS@cabot-corp.com

Emergency Telephone Number: UK (Cabot Carbon Ltd - Barry): (+44) 1446-709 641

Germany (Cabot GmbH - Rheinfelden): (+49) 7623-7070

China: (86-792) 3170175

Canada: CANUTEC 1-613-996-6666

US: CHEMTREC: +1-703-527-3887 or 1-800-424-9300

2. HAZARDS IDENTIFICATION

Indication of danger: Not a hazardous substance according to EC-Directive 67/548/EC, its various

amendments and adaptations and EC-Regulation 1272/2008 (CLP)

Inhalation, Skin contact, Eye contact **Principle Routes of Exposure:**

POTENTIAL HEALTH EFFECTS

Eye Contact: May cause mechanical irritation.

Skin Contact: Repeated exposure may cause skin dryness or cracking. Inhalation: Dust may be irritating to respiratory tract. Provide appropriate exhaust ventilation at

machinery and at places where dust can be generated. See also Section 8.

Ingestion: Health injuries are not known or expected under normal use.

Does not contain any substances greater than 0.1% listed by IARC (International Carcinogenic Effects:

Agency for Research on Cancer), NTP (National Toxicology Program), OSHA (Occupational Safety and Health Administration), ACGIH (American Conference for Governmental Industrial Hygienists) or EU (European Union). See also Section 11.

Target Organ Effects: Lungs

Medical Conditions Aggravated

by Exposure:

Asthma, Respiratory disorder

Potential Environmental Effects: No special environmental precautions required.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	EINECS/ELINCS Number	Weight %	EU Classification
Synthetic Amorphous, Pyrogenic Silica	112945-52-5	*	> 99.9	None

^{*} See Section 15.

4. FIRST AID MEASURES

Skin Contact: Wash thoroughly with soap and water. Seek medical attention if redness, swelling,

itching, or burning occurs.

Eye Contact: Flush eyes immediately with large amounts of water for 15 minutes. Seek medical

attention if redness, swelling, itching, burning or visual disturbances occur.

Inhalation: If cough, shortness of breath or other breathing problems occur, move to fresh air.

Seek medical attention if symptoms persist. If necessary, restore normal breathing

through standard first aid measures.

Do not induce vomiting. If conscious, give several glasses of water. Never give Ingestion:

anything by mouth to an unconscious person.

Treat symptomatically. Notes to Physician:

5. FIRE-FIGHTING MEASURES

Use extinguishing measures that are appropriate to local circumstances and the **Extinguishing Media:**

surrounding environment.

Firefighters:

Special Protective Equipment for Wear suitable protective equipment. In the event of fire, wear self-contained

breathing apparatus.

Specific Hazards: Product resists ignition and does not promote flame spread.

Hazardous Decomposition and/or None.

Combustion Products:

This material is an inorganic dust and will not create nor support conditions that **Risk of Dust Explosion:**

would result in a dust explosion or fire.

Product Name: CAB-O-SIL® Untreated Fumed Silica Product Code: M5

Revision Date: 08/September/2011

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid dust formation. Ensure adequate ventilation. Use personal protective

equipment. See also Section 8.

Methods for Cleaning Up: Clean up promptly by vacuum. Use a suitable vacuum cleaner. Do not create a dust

cloud by using a brush or compressed air. Pick up and transfer to properly labelled

containers. See Section 13.

Environmental Precautions: No special environmental precautions required. Local authorities should be advised if

significant spillages cannot be contained.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. Avoid dust formation. Do not breathe dust. Provide

> appropriate exhaust ventilation at machinery and at places where dust can be generated. Do not create a dust cloud by using a brush or compressed air. Take precautionary measures against static discharge. All metal parts of the mixing and processing equipment must be earthed/grounded. Ensure all equipment is electrically

earthed/grounded before beginning transfer operations.

Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store Storage:

together with volatile chemicals as they may be adsorbed onto product. Keep at

ambient temperatures.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS

Amorphous Silica, The regulatory Australia: 2 mg/m³, TWA, Respirable **exposure limits are found under** Austria MAK: 4 mg/m³, TWA, Inhalable fraction

the general silica, CAS RN 7631- Finland:

86-9:

5 ma/m³

4 mg/m³, TWA, Inhalable fraction (a) Germany TRGS 900:

India: 10 mg/m³, TWA

Ireland: 2.4 mg/m³, TWA, Respirable dust Norway: 1.5 mg/m³, TWA, Respirable dust

Switzerland: 4 mg/m³, TWA, Inhalable UK WEL: 6 mg/m³, TWA, Inhalable 2.4 mg/m³, TWA, Respirable

Dust, or Particulates Not Otherwise Specified:

Belgium: 10 mg/m³, TWA, Inhalable

3 mg/m³, TWA, Respirable

China: 8 mg/m³, TWA

10 mg/m³, STEL

10 mg/m³, TWA Inhalable dust France:

> 5 mg/m³, TWA Respirable dust 10 mg/m³, TWA, Inhalable

Italy: 3 mg/m³, TWA, Respirable Malaysia:

10 mg/m³, TWA, Inhalable 3 mg/m³, TWA, Respirable

10 mg/m³, VLA, Inhalable Spain:

3 mg/m³, VLA, Respirable

US ACGIH - TLV: 10 mg/m³, TWA, Inhalable

3 mg/m³, TWA, Respirable

US OSHA - PEL: 15 mg/m³, TWA, Total dust 5 mg/m³, TWA, Respirable

Revision Date: 08/September/2011

(a) - In its facilities globally, Cabot Corporation manages to the Germany TRGS 900 occupational exposure limit of 4 mg/m³, TWA, Inhalable fraction

MAK: Maximale Arbeitsplatzkonzentration (Maximum Workplace Concentration)

OEL: Occupational Exposure Limit PEL: Permissible Exposure Limit STEL: Short Term Exposure Limit TLV: Threshold Limit Value

TRGS: Technische Regeln für Gefahrstoffe (Technical Rule for Hazardous Materials)

TWA: Time Weighted Average

US ACGIH: United States American Conference of Governmental Industrial Hygienists

US OSHA: United States Occupational Safety and Health Administration

VLA: Valore Límite Ambientales (Environmental Limit Value)

WEL: Workplace Exposure Limit

DNEL: As required under the EU Registration, Evaluation and Authorization of Chemicals

(REACH) Regulation, the Synthetic Amorphous Silica REACH Consortium (of which Cabot Corporation is a member) developed a Derived No Effect Level (DNEL) for Synthetic Amorphous Silica of 4 mg/m³ inhalable (Germany TRGS 900 occupational

exposure limit)

ENGINEERING CONTROLS Ensure adequate ventilation to maintain exposures below occupational limits.

Provide appropriate exhaust ventilation at machinery and at places where dust can

be generated.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection: Approved respirator may be necessary if local exhaust ventilation is not adequate.

Hand Protection: Repeated exposure may cause skin dryness or cracking. Use appropriate protective

barrier before handling.

Eye Protection: Wear eye/face protection.

Skin and Body Protection: Wear suitable protective clothing.

Other: Handle in accordance with good industrial hygiene and safety practice. Emergency

eyewash and safety shower should be located nearby.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White Powder

Odor: None

Odor Threshold: Not applicable

pH: 3.6 - 4.5

Relative Density: Not determined

Bulk Density: 30-150 kg/m³

Specific Gravity: 2.2 g/cm³ @ 20°C

Vapor Density: Not applicable

Boiling Point/Range: 2230°C

Melting Point/Range: 1700°C

Vapor Pressure: Not applicable

Product Name: CAB-O-SIL® Untreated Fumed Silica Product Code: M5 Revision Date: 08/September/2011 Page 5 of 8

Water Solubility: Insoluble

% Volatile (by Weight): Not applicable

Evaporation Rate: Not applicable

Viscosity: Not applicable

Partition Coefficient (n-octanol/water): Not determined

Flash Point: Not determined

Explosion Limits in Air - Upper (g/m³):Not applicable Explosion Limits in Air - Lower (g/m³):
Not applicable

Autoignition Temperature: Not applicable

Flammability Classification: Not applicable

Decomposition Temperature: Not determined

Oxidizing Properties: Not applicable

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to Avoid: None reported.

Hazardous Decomposition and/or None.

Combustion Products:

Static Discharge Effects: Take precautionary measures against static discharges. Avoid dust formation. All

metal parts of the mixing and processing equipment must be earthed/grounded. Ensure all equipment is electrically earthed/grounded before beginning transfer operations. This material is an inorganic dust and will not create nor support

conditions that would result in a dust explosion or fire.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Oral LD50: LD50/oral/rat = > 5000 mg/kg.

Inhalation LC50: Due to the product's physical characteristics, no suitable testing procedure is available.

Dermal LD50: LD50/dermal/rabbit = > 2000 mg/kg.

STOT - Single Exposure: None observed.

Eye Irritation: Draize score 1.0/110 @ 24 hr.

Skin Irritation: Primary irritation index = 0/8 @ 24 hr

SUBCHRONIC TOXICITY

No significant treatment-related adverse effects were observed in rats administered silica at doses of up to 8% silica in their diet for a duration of 2 weeks to 6 months.

Revision Date: 08/September/2011

Product Name: CAB-O-SIL® Untreated Fumed Silica Product Code: M5

STOT - Repeated Exposure: None expected

CHRONIC TOXICITY

Mutagenic Effects:

Not mutagenic in AMES Test, Negative in the unscheduled DNA synthesis assay, Negative in the chromosome aberration test in Chinese hamster ovary (CHO) cells.

Reproductive Toxicity: Did not show teratogenic effects in animal experiments. According to experience not expected.

Sensitization: According to experience, sensitization is not expected.

Synergistic Materials: None reasonably foreseeable.

Carcinogenic Effects: Does not contain any substances greater than 0.1% listed by IARC (International Agency for Research on Cancer), NTP (National Toxicology Program), OSHA (Occupational Safety and Health Administration), ACGIH (American Conference for Governmental Industrial Hygienists) or EU (European Union).

Aspiration Hazard: Not determined

12. ECOLOGICAL INFORMATION

Aquatic Toxicity: Fish (Brachydanio rerio) LC50 (96 h): > 10,000 mg/l; (Method: OECD 203)

ENVIRONMENTAL FATE

Mobility: Not expected to migrate.

Bioaccumulation: Not expected due to physicochemical properties of the substance.

Persistence / Degradability: The methods for determining biodegradability are not applicable to inorganic

substances

Distribution to Environmental

Compartments:

Not determined.

PBT and vPvB Assessment: This substance does not fulfill the criteria for PBT or vPvB

Other adverse effects: No other data are available

13. DISPOSAL CONSIDERATIONS

Disclaimer: Information in this section pertains to the product as shipped in its intended composition as described in Section 3 of this MSDS. Contamination or processing may change waste characteristics and requirements. Regulations may also apply to empty containers, liners or rinsate. State/provincial and local regulations may be different from federal regulations.

Dispose of in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

UN Number: Not regulated

UN Proper Shipping Name: Not regulated

UN Shipping Class: Not regulated

UN Packing Group: Not regulated

Product Name: CAB-O-SIL® Untreated Fumed Silica Product Code: M5

IMDG (International Maritime Organization's Dangerous Goods Code):

Use UN classification listed above.

IATA:

Use UN classification listed above.

15. REGULATORY INFORMATION

Regulatory information is found under the general silica: CAS RN 7631-86-9, EINECS RN 231-545-4.

<u>Indication of danger:</u> Not a hazardous substance according to EC-Directive 67/548/EC, its various amendments and adaptations and EC-Regulation 1272/2008 (CLP).

EU Chemical Safety Assessment:

Per Article 14.1 of the REACH Regulation a Chemical Safety Assessment has been carried out.

EU Exposure Scenarios

Per Article 14.4 of the REACH Regulation no exposure scenario has been developed as the substance is not hazardous.

International Inventories

All components of this product are listed on or exempt from the following inventories:

- YES Australian Inventory of Chemical Substances (AICS)
- YES Canadian Domestic Substances List (DSL)
- YES Chinese Inventory
- YES European Inventory of Existing Commercial Chemical Substances (EINECS)
- YES Japanese Existing and New Chemical Substances (ENCS)
- YES Korean Existing Chemicals List (KECL)
- YES New Zealand Hazardous Substances and New Organisms Act (HSNO)
- YES Philippine Inventory of Chemicals and Chemical Substances (PICCS)
- YES United States Toxic Substances Control Act (TSCA) Inventory

Germany Water Endangering Class (WGK) Class

Chemical Name

Synthetic Amorphous, nwg (not water endangering): 849

Pyrogenic Silica

Switzerland Giftklasse (Poison Class)Toxic Category

Chemical Name

Synthetic Amorphous, -- (tested and found to be not toxic): G-8311

Pyrogenic Silica

16. OTHER INFORMATION

Prepared by: Cabot Corporation - Safety, Health and Environmental Affairs

Revision Date: 08/September/2011 **Previous Revision Date:** 16/December/2010

Reason for Revision: Revisions to Section(s) 1, 8, 15

Cabot Corporation

Product Name: CAB-O-SIL® Untreated Furned Silica Product Code: M5 Revision Date: 08/September/2011 Page 8 of 8

Disclaimer:

The information set forth is based on information that Cabot Corporation believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and Cabot assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

® and 'TM' indicate trademarks of the Cabot Corporation.