

## Safety Data Sheet

YKF684

TOPLAC ATLANTIC GREY 289

Version No. 10 Date Last Revised 26/08/05

### 1. Identification of the preparation and company

<b>Preparation/Product Name</b>	TOPLAC ATLANTIC GREY 289
<b>Product Code</b>	YKF684
<b>HSE Number</b>	
<b>Intended use</b>	
<b>Application Method</b>	
<b>Company Name</b>	International Paint Stoneygate Lane Felling Gateshead Tyne and Wear NE10 OJY UK
<b>Telephone No.</b>	+44 (0)191 469 6111
<b>Fax No.</b>	+44 (0)191 438 3711
<b>24 hour Emergency Telephone No.</b>	+44 (0)191 469 6111
<b>Official Advisory Body Telephone No.</b>	+44 (0)870 600 6266 For Advice to Doctors & Hospitals only

### 2. Composition/information on ingredients

If the product contains substances that present a health hazard within the meaning of the Dangerous Substances Directive 67/548/EC, or have occupational exposure limits detailed in EH40, these substances are listed below.

Ingredient	EINECS	Concentration	Symbol(s)	Risk phrases (*)
2-Butanone oxime	202-496-6	0 - < 1	Xn	R40, R21, R41, R43
Cobalt carboxylate	237-015-9	0 - < 1	Xn,N	R22, R38, R43, R51-53
Naphtha (petroleum), hydrodesulfurized heavy	265-185-4	10 - < 25	Xn,N	R51-53, R65, R66
Naphtha (petroleum), hydrotreated heavy	265-150-3	1 - < 2.5	Xn	R65, R66

\* The full texts of the phrases are shown in section 16.



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : [www.yachtpaint.com](http://www.yachtpaint.com) , [www.international-marine.com](http://www.international-marine.com) , [www.international-pc.com](http://www.international-pc.com)

**Safety Data Sheet**

YKF684

TOPLAC ATLANTIC GREY 289

Version No. 10 Date Last Revised 26/08/05

**3. Hazard identification of the product**

Flammable.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Further information is given in section 11.

**4. First aid measures****General**

In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

**Inhalation**

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

**Eye Contact**

Irrigate copiously with clean fresh water for at least 10 minutes, holding the eyelids apart and seek medical attention.

**Skin Contact**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognised skin cleanser. Do NOT use solvents or thinners.

**Ingestion**

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : [www.yachtpaint.com](http://www.yachtpaint.com) , [www.international-marine.com](http://www.international-marine.com) , [www.international-pc.com](http://www.international-pc.com)

**Safety Data Sheet**

YKF684

TOPLAC ATLANTIC GREY 289

Version No. 10 Date Last Revised 26/08/05

**5. Fire-fighting measures**

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub> powder, water spray.

Do not use; water jet.

Note; Fire will produce dense black smoke. Decomposition products may be hazardous to health. Avoid exposure and use breathing apparatus as appropriate.

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

**6. Accidental release measures**

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapour levels are below the Lower Explosive Limit before re-entering.

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the local water company immediately. In the case of contamination of rivers, streams or lakes the Environmental Protection Agency should also be informed.



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : [www.yachtpaint.com](http://www.yachtpaint.com) , [www.international-marine.com](http://www.international-marine.com) , [www.international-pc.com](http://www.international-pc.com)

**Safety Data Sheet**

YKF684

TOPLAC ATLANTIC GREY 289

Version No. 10 Date Last Revised 26/08/05

**7. Handling and storage****Handling**

This coating contains solvents. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Areas of storage, preparation and application should be ventilated to prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

**In Storage**

Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

**In Use**

Avoid skin and eye contact. Avoid inhalation of vapours and spray mists. Observe label precautions. Use personal protection as shown in section 8.

Smoking, eating and drinking should be prohibited in all preparation and application areas.

Never use pressure to empty a container; containers are not pressure vessels.

All sources of ignition (hot surfaces, sparks, open flames etc) should be excluded from areas of preparation and application. All electrical equipment (including torches) should be protected (Ex) to the appropriate standard.

The product may charge electrostatically. Always use earthing leads when pouring solvents and transferring product.

Operators should wear clothing which does not generate static (at least 60% natural fibre) and antistatic footwear; floors should be of conducting type.

Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards.

**Storage**

Store in a well ventilated, dry place away from sources of heat and direct sunlight.

Store on concrete or other impervious floor, preferably with bunding to contain any spillage. Do not stack more than 3 pallets high.

Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in the original container or one of the same material.

Prevent unauthorised access.



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : [www.yachtpaint.com](http://www.yachtpaint.com) , [www.international-marine.com](http://www.international-marine.com), [www.international-pc.com](http://www.international-pc.com)

## Safety Data Sheet

YKF684

TOPLAC ATLANTIC GREY 289

Version No. 10 Date Last Revised 26/08/05

### 8. Exposure controls and personal protection

#### Engineering Measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

#### Exposure Limits

The following workplace exposure limits have been established by the Health and Safety Executive as published in EH40.

Material	Short term (15 min. ave)		Long term (8hr time weighted average)	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Naphtha (petroleum), hydrodesulfurized heavy			600	R
Naphtha (petroleum), hydrotreated heavy			1000	

(C) Capable of causing cancer and/or heritable genetic damage

(R) Suppliers recommended limit

(S) Capable of causing occupational asthma

(+) There is a risk of absorption through unbroken skin.

#### Personal Protection

##### Respiratory Protection

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators. When spraying this product use a respiratory mask with charcoal and dust filters (as filter combination A2-P2). In confined spaces use compressed air or fresh air respiratory equipment.

##### Eye Protection

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids. Eyewear should comply with British Standard 2092.

##### Hand Protection

Nitrile rubber gloves should be worn during mixing and application.

##### Skin Protection

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. Barrier creams may help to protect areas which are difficult to cover such as the face and neck. They should however not be applied once exposure has occurred. Petroleum jelly based types such as Vaseline should not be used. All parts of the body should be washed after contact.



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : [www.yachtpaint.com](http://www.yachtpaint.com) , [www.international-marine.com](http://www.international-marine.com) , [www.international-pc.com](http://www.international-pc.com)

## Safety Data Sheet

YKF684

TOPLAC ATLANTIC GREY 289

Version No. 10 Date Last Revised 26/08/05

### 9. Physical and chemical properties

Physical State	Liquid
Flash Point (deg C)	42
Viscosity (cSt)	280
Specific Gravity	1.23552
Vapour Density	Heavier than air.
Lower Explosive Limit	.6
Solubility in Water	Immiscible
R.A.Q. to ventilate to 10% of the LEL (m <sup>3</sup> /l)	86.41

### 10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7). When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid possible exothermic reactions.

### 11. Toxicological information

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 15 for details.

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : [www.yachtpaint.com](http://www.yachtpaint.com) , [www.international-marine.com](http://www.international-marine.com), [www.international-pc.com](http://www.international-pc.com)

**Safety Data Sheet**

YKF684

TOPLAC ATLANTIC GREY 289

Version No. 10 Date Last Revised 26/08/05

**12. Ecological information**

There are no data available on the product itself.

The product should not be allowed to enter drains or water courses.

Petroleum naphtha: Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment

**13. Disposal considerations**

Do not allow into drains or water courses. Wastes and empty containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

European Waste Catalogue Number

08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances

**14. Transport information**

Transport only in accordance with the following regulations:

ADR/RID UN1263 Paint, 3, III

IMDG	Class	3	Subsidiary Class
	Proper Shipping Name	PAINT	
	UN No	1263	
	Ems	F-E,S-E	
	Packaging Group	III	
	Marine Pollutant	Yes	

ICAO/IATA	Shipping Name	PAINT
	Class	3
	UN No	1263
	Packaging Group	III



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : [www.yachtpaint.com](http://www.yachtpaint.com) , [www.international-marine.com](http://www.international-marine.com) , [www.international-pc.com](http://www.international-pc.com)

**Safety Data Sheet**

YKF684

TOPLAC ATLANTIC GREY 289

Version No. 10 Date Last Revised 26/08/05

**15. Regulatory information**

In accordance with EC Directive 88/379/EEC and the Chemicals (Hazard Information and Packaging for Supply) Regulations SI /3247/1994 this product is labelled as follows:

**Symbol(s)****Contains;****R. Phrases;**

Flammable.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**S. Phrases;**

Keep out of the reach of children.

Do not breathe vapour/spray.

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

**P. Phrases;**

Contains 2-butanone oxime, cobalt carboxylate. May produce an allergic reaction



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : [www.yachtpaint.com](http://www.yachtpaint.com) , [www.international-marine.com](http://www.international-marine.com), [www.international-pc.com](http://www.international-pc.com)



**Safety Data Sheet**

YKF684

TOPLAC ATLANTIC GREY 289

Version No. 10 Date Last Revised 26/08/05

**16. Other information**

The information on this MSDS is based upon the present state of our knowledge and on current EEC and national laws.

The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

The information in this Health & Safety Data Sheet is required pursuant to Directive 91/155/EEC and the Chemicals (Hazard Information & Packaging for Supply) Regulations 1994.

The full text of the R phrases appearing in section 2 is:

R21 Harmful in contact with skin.

R22 Harmful if swallowed.

R38 Irritating to skin.

R40 Limited evidence of a carcinogenic effect.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R51-53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : [www.yachtpaint.com](http://www.yachtpaint.com) , [www.international-marine.com](http://www.international-marine.com), [www.international-pc.com](http://www.international-pc.com)