

# West & Senior Limited

Milltown Street • Radcliffe • Manchester • M26 1WE • United Kingdom Tel +44 (0) 161 724 7131 • Fax +44 (0) 161 724 9519 http://www.westsenior.co.uk • info@westsenior.co.uk

## 

### PY GAZELLE BS08B21 PIGMENT

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking	
1.1. Product identifier	
Product name	PY GAZELLE BS08B21 PIGMENT
Product number	WS10097A
1.2. Relevant identified uses	s of the substance or mixture and uses advised against
Identified uses	COLOURING OF POLYESTER RESINS & GELCOATS.
1.3. Details of the supplier of the safety data sheet	
Supplier	WEST AND SENIOR LIMITED. MILLTOWN STREET RADCLIFFE MANCHESTER. M26 1WE. TEL + 44 01617247131 FAX + 44 01617249519 info@westsenior.co.uk
1.4. Emergency telephone number	
Emergency telephone	24 HOUR EMERGENCY TELEPHONE NUMBER : + 44 (0) 7930 595916
SECTION 2: Hazards identit	fication
2.1. Classification of the sub	ostance or mixture
Classification (EC 1272/200	<u>8)</u>
Physical hazards	Not Classified
Health hazards	Not Classified
Environmental hazards	Not Classified
Environmental 2.2. Label elements	The product is not expected to be hazardous to the environment.
Hazard statements	NC Not Classified
Supplemental label information	EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
2.3. Other hazards	in any substances classified as PBT or vPvB

This product does not contain any substances classified as PBT or vPvB.

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

TITANIUM DIOXIDE CAS number: 13463-67-7	EC number: 236-675-5	<b>30-60%</b> REACH registration number: 01-
		2119489379-17-0000
Classification Not Classified		
BARIUM SULPHATE		5-10%
CAS number: 7727-43-7	EC number: 231-784-4	REACH registration number: 01- 2119491274-35-0001
Classification Not Classified		
C.I. PIGMENT YELLOW 42		5-10%
CAS number: 51274-00-1	EC number: 257-098-5	REACH registration number: 01- 2119457554-33-0000
Classification Not Classified		
RED OXIDE C.I. PIGMENT F	RED 101	1-5%
CAS number: 1309-37-1	EC number: 215-168-2	REACH registration number: 01- 2119457614-35-0011
Classification Not Classified		
The full text for all hazard state	ements is displayed in Section 16.	
Composition comments		le (CAS 13463-67-7) The Annex VI classification o ture according to its Note 10. No other disclosure
SECTION 4: First aid measure	95	
4.1. Description of first aid me	asures	
General information	No specific recommendations. If in doubt, g	et medical attention promptly.
Inhalation	Move affected person to fresh air at once. C	Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an uncons mouth thoroughly with water. Give plenty of discomfort continues.	cious person. Do not induce vomiting. Rinse water to drink. Get medical attention if any
Skin contact	Remove affected person from source of cor persists after washing.	ntamination. Get medical attention if irritation
Eye contact	minutes. Continue to rinse for at least 15 m	ds wide apart. Continue to rinse for at least 15 inutes. Get medical attention if any discomfort
	continues.	

General information Get medical attention if any discomfort continues.

Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.
Eye contact	No specific symptoms known.
4.3. Indication of any immedia	te medical attention and special treatment needed
Notes for the doctor	No specific recommendations.
SECTION 5: Firefighting mean	sures
5.1. Extinguishing media	
Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising fr	rom the substance or mixture
Specific hazards	No unusual fire or explosion hazards noted.
Hazardous combustion products	Heating may generate flammable vapours. Vapours may form explosive mixtures with air.
5.3. Advice for firefighters	
Protective actions during firefighting	No specific firefighting precautions known.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
SECTION 6: Accidental release	se measures
6.1. Personal precautions, pro	ptective equipment and emergency procedures
Personal precautions	Avoid heat, flames and other sources of ignition. Provide adequate ventilation.
6.2. Environmental precaution	<u>is</u>
Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses.
6.3. Methods and material for	containment and cleaning up
Methods for cleaning up	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses.
6.4. Reference to other section	ns
Reference to other sections	For waste disposal, see section 13.
SECTION 7: Handling and storage	
7.1. Precautions for safe hand	lling
Usage precautions	Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Take precautionary measures against static discharges. Contaminated rags and cloths must be put in fireproof containers for disposal.
7.2. Conditions for safe storage	ge, including any incompatibilities
Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep
	separate from food, feedstuffs, fertilisers and other sensitive material.

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

#### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

#### Occupational exposure limits

#### TITANIUM DIOXIDE

EH40 WEL, Time Weighted Average (TWA):, Inhalable dust. 10 mg/m3, 8 h EH40 WEL, Time Weighted Average (TWA):, Respirable dust. 4 mg/m3, 8 h

#### **BARIUM SULPHATE**

Long-term exposure limit (8-hour TWA): 4 mg/m<sup>3</sup> respirable dust Long-term exposure limit (8-hour TWA): 10 mg/m<sup>3</sup> inhalable dust

#### C.I. PIGMENT YELLOW 42

Long-term exposure limit (8-hour TWA): 5 mg/m<sup>3</sup>, Iron. fume Short-term exposure limit (15-minute): 10 mg/m<sup>3</sup>, Iron. fume

#### **RED OXIDE C.I. PIGMENT RED 101**

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> respirable dust Long-term exposure limit (8-hour TWA): WEL 5 mg/m<sup>3</sup> fume Short-term exposure limit (15-minute): WEL 10 mg/m<sup>3</sup> fume as Fe

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

#### CARBON BLACK

Argentina 3.5, TWA Australia 3.0, TWA, inhalable Belgium 3.6, TWA Brazil 3.5, TWA Canada (Ontario) 3.0 TWA, inhalable China 4.0, TWA 8.0, TWA, STEL (15 min) Colombia 3.0, TWA, inhalable Czech Republic 2.0, TWA Egypt 3.5, TWA Finland 3.5, TWA; 7.0, STEL France - INRS 3.5, TWA/VME inhalable Germany – BeKGS527 0.5, TWA, respirable; 2.0, TWA, inhalable (DNEL values) Hong Kong 3.5, TWA Indonesia 3.5, TWA/NABs Ireland 3.5, TWA; 7.0, STEL Italy 3.5, TWA, inhalable Japan - MHLW 3.0 Japan – SOH 4.0, TWA; 1.0, TWA, respirable Korea 3.5, TWA Malaysia 3.5, TWA Mexico 3.5, TWA Russia 4.0, TWA Spain 3.5, TWA (VLA-ED) Sweden 3.0, TWA United Kingdom 3.5, TWA, inhalable; 7.0, STEL, inhalable EU REACH DNEL 2.0, TWA, inhalable; 0.5, TWA respirable United States 3.5, TWA, OSHA-PEL 3.0, TWA, ACGIH-TLV®, inhalable 3.5, TWA, NIOSH-REL WEL = Workplace Exposure Limit.

Ingredient comments	No exposure limits known for ingredient(s).
	TITANIUM DIOXIDE (CAS: 13463-67-7)
DNEL	Workers - Inhalation; Long term local effects: 10 mg/m³ Professional - Inhalation; Long term local effects: 10 mg/m³ Consumer - Oral; Long term systemic effects: 700 mg/kg/day
PNEC	marine water; 0.0184 mg/l Fresh water; 0.184 mg/l Intermittent release; 0.193 mg/l STP; 100 mg/l Sediment, marine water; 100 mg/kg Sediment, Fresh water; 1000 mg/kg Soil; 100 mg/kg
	BARIUM SULPHATE (CAS: 7727-43-7)
DNEL	Workers - Inhalation; Long term systemic effects: 10 mg/m³ Workers - Inhalation; Long term local effects: 10 mg/m³ Consumer - Inhalation; Long term systemic effects: 10 mg/m³ Consumer - Oral; Long term systemic effects: 13000 mg/kg
PNEC	Fresh water; 115 μg/l STP; 62.2 mg/l Sediment (Freshwater); 600.4 mg/kg Soil; 207.7 mg/kg
	C.I. PIGMENT YELLOW 42 (CAS: 51274-00-1)
DNEL	Workers - Inhalation; Long term local effects: 10 mg/cm <sup>2</sup>
	RED OXIDE C.I. PIGMENT RED 101 (CAS: 1309-37-1)
DNEL	Workers - Inhalation; Long term systemic effects: 10 mg/m <sup>3</sup> Workers - Inhalation; Long term local effects: 10 mg/m <sup>3</sup>
	CARBON BLACK (CAS: 1333-86-4)
DNEL	Workers - Inhalation; Long term : 0.5 mg/m <sup>3</sup> , respirable fraction Workers - Inhalation; Long term : 2 mg/m <sup>3</sup> , inhalable fraction
	Trimethylolpropane (CAS: 77-99-6)
DNEL	Workers - Inhalation; Long term systemic effects: 3.3 mg/m <sup>3</sup> Workers - Dermal; Long term systemic effects: 0.94 mg/kg Consumer - Inhalation; Long term systemic effects: 0.58 mg/m <sup>3</sup> Consumer - Dermal; Long term systemic effects: 0.34 mg/kg Consumer - Oral; Long term systemic effects: 0.34 mg/kg
8.2. Exposure controls	

8.2. Exposure controls



Appropriate engineering controls	No specific ventilation requirements.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid. or Coloured paste.
Colour	Various colours.
Odour	Aromatic.
Odour threshold	No information available.
рН	No information available.
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	>65°C
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	No information available.
Other flammability	No information available.
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	No information available.
Bulk density	No information available.
Solubility(ies)	Organic solvents. Insoluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.

Explosive under the influence of a flame	No
Oxidising properties	Not available.
Comments	No information available.
9.2. Other information	
Other information	No information required.
SECTION 10: Stability and rea	activity
10.1. Reactivity	
Reactivity	There are no known reactivity hazards associated with this product.
10.2. Chemical stability	
Stability	Stable at normal ambient temperatures.
10.3. Possibility of hazardous	reactions
Possibility of hazardous reactions	No potentially hazardous reactions known.
10.4. Conditions to avoid	
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.
10.5. Incompatible materials	
Materials to avoid	No information available.
10.6. Hazardous decompositio	on products
Hazardous decomposition products	Thermal decomposition may lead to formation of a multiplicity of compounds some of which may be hazardous. With incomplete combustion smoke and hazardous fumes and gases , including carbon monoxide, may be formed.
SECTION 11: Toxicological int	formation
11.1. Information on toxicologi	cal effects
Toxicological effects	Not classified.
Acute toxicity - oral Notes (oral LD₅o)	Not relevant.
Acute toxicity - dermal Notes (dermal LD <sub>50</sub> )	Not relevant.
Acute toxicity - inhalation Notes (inhalation LC <sub>50</sub> )	Not relevant.
Acute and chronic health hazards	No specific health hazards known.
Toxicological information on ingredients.	
Toxicological information on in	gredients.
Toxicological information on in	GARBON BLACK
Toxicological information on in Acute toxicity - or	CARBON BLACK

Germ cell mutage	enicity
Summary	In vivo mutagenicity in rats occurs by mechanisms secondary to a threshold effect and is a consequence of "lung overload," which leads to chronic inflammation and the release of genotoxic oxygen species. This mechanism is considered to be a secondary genotoxic effect and, thus, carbon black itself would not be considered to be mutagenic.
Genotoxicity - in	vitro Carbon black is not suitable to be tested directly in bacterial (Ames test) and other in vitro systems because of its insolubility. However, when organic solvent extracts of carbon black have been tested, results showed no mutagenic effects. Organic solvent extracts of carbon black can contain traces of polycyclic aromatic hydrocarbons (PAHs). A study to examine the bioavailability of these PAHs showed that they are very tightly bound to carbon black and are not bioavailable (Borm, 2005).
Genotoxicity - in	vivo In an experimental investigation, mutational changes in the hprt ene were reported in alveolar epithelial cells in the rat following inhalation exposure to carbon black (Driscoll, 1997). This observation is considered to be rat-specific and a consequence of "lung overload," which leads to chronic inflammation and release of reactive oxygen species. This is considered to be a secondary genotoxic effect and, thus, carbon black itself would not be considered to be mutagenic.
Carcinogenicity	
IARC carcinogen	icity IARC Group 2B Possibly carcinogenic to humans.
SECTION 12: Ecological infor	mation
Ecotoxicity	Not regarded as dangerous for the environment.
12.1. Toxicity	
Toxicity	Not considered toxic to fish.
12.2. Persistence and degrada	ability
Persistence and degradability	There are no data on the degradability of this product.
12.3. Bioaccumulative potentia	al
Partition coefficient	– Not available.
12.4. Mobility in soil	
Mobility	No information available.
12.5. Results of PBT and vPvI	3 assessment
Results of PBT and vPvB assessment	No information available.
12.6. Other adverse effects	
Other adverse effects	None known.
SECTION 13: Disposal consid	erations
13.1. Waste treatment method	is
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Empty containers should be taken to an approved waste

handling site for recycling or disposal.

#### SECTION 14: Transport information

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

#### 14.1. UN number

Not applicable.

#### 14.2. UN proper shipping name

Not applicable.

#### 14.3. Transport hazard class(es)

Not applicable.

#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

# Environmentally hazardous substance/marine pollutant No.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not relevant. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information	
15.1. Safety, health and e	nvironmental regulations/legislation specific for the substance or mixture
National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.
Guidance	A guide to local exhaust ventilation (LEV) HSG258 (as ammended) Workplace Exposure Limits EH40.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

7

SECTION 16: Other information	
Revision date	22/11/2021

Revision

Supersedes date 17/07/2018

The information contained within this document is presented in good faith and is believed to be correct. West and Senior Limited makes no representation as to the accuracy and/or completeness of this information. This information is issued on the condition that the user will determine the safety and suitability of products for their purposes prior to use. All technical details and values presented are deemed typical and do not constitute a delivery specification.