



INDASA

HEALTH AND SAFETY PRODUCT INFORMATION

Product: P.U. Sealer (black/grey/white)

Date: 1st May 2009

Product code: 472576/472583/472590

Page 1 of 4

1.

Company Name and Address	
INDASA Abrasives (UK) Limited, Viking Works, Greenstead Road, Colchester Essex CO1 2ST Tel : 01206 870366 Fax : 01206 860525 Email : office@indasa.co.uk	

2.

Composition/Information on ingredients				
Global description	Expansion joint sealant and adhesive			
Components that may contribute to hazards				
Name	CAS-Nr.	Symbol	RangeW/W %	R-phrases
Diphenylmethane4.4'Diisocyanate	101-68-8	Xn	1-5	R20-36/37/38-42/43
Calcium Oxide	1305-78-8	Xi	1-2.5	R37/38-41
Solvent Naphta light aromatic	64742-95-6	Xn	2.5-10	R10-37-51/53-65-66

3.

Hazards identification	
Specific hazards	
R-phrases	Description
42/43 52/53	May cause sensitization by inhalation and by skin contact Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment

4.

First-Aid measures	
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advise.
Skin	Wash with plenty of soap and water, if necessary take off dirty clothing. Do not use solvents or thinners.
Eyes	Rinse with plenty of water for 10 minutes holding the eyelids open. Seek medical advice in all cases with the label.
Ingestion	Wash out mouth and seek medical advice with the label. Do not induce vomiting.

5.

Fire-Fighting measures	
Extinguishing media	
Use	Water Spray, CO₂ powders, foam
Don't use	Water jet
Specific hazards	
A fire will often produce a thick black smoke, exposure to which can be harmful to health.	
Specific methods	
Protection of firefighters	
Wear autonomous insulating breathing apparatus. Cool closed containers exposed to fire with water.	

6.

Accident release measures	
Personal precautions	
Ventilate the area. Avoid breathing vapours. Refer to protective measures listed in 7 and 8.	
Environmental precautions	
If the product contaminates lake, rivers and sewage, inform appropriate authorities in accordance with local regulations. Do not allow to enter drains or water courses	
Methods for cleaning-up	
Collect mechanically the preparation and place in container. One possible decontaminate comprises: Water/ethanol or IPA/Ammonia solution (45/50/5 by volume). Once this stage reached, close container and dispose according to local regulations. Do not allow to enter drains or watercourses.	

7.

Handling and storage	
Handling	Handle in well ventilated areas. Anyone with a history of asthma, allergies, chronic or periodic respiratory problems must on no account use these preparations. CO₂ will be formed which in closed containers can result in pressurization. Care should be taken when re-opening partly used containers. Avoid skin and eye contact and the inhalation of vapours. Smoking, eating, drinking should be prohibited in application area. Never use pressure to empty. Comply with the health and safety at work laws.
Storage	Keep tightly closed in a dry place. Store between +5 and +25° in a dry, well ventilated area. Keep away from oxidizing agent, from strongly acid materials as well as amines, alcohol's and water. No smoking, eating or drinking. Containers, which are opened, must be carefully resealed and kept upright to prevent leakage.

8.

Exposure controls/personal protection		
Name	VLE (15mins)	VME (8j/j)
Solvent Naphta light aromatic		50 PPM 254 mg/m³
Diphenylmethane Diisocyanate	0.02PPM - 0.2mg/m³	0.01 PPM 0.1 mg/m³
Protection		
Anyone with a history of asthma, allergies, chronic or periodic respiratory problems must on no account use these preparations. Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.		
Respiratory	Ventilation and suitable approved masks in areas of high concentrations	
Hand	For prolonged or repeated handling, use polyvinyl gloves. Barrier	

	creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.
Eye	Safety glasses
Skin and body	Protective clothing

9.

Physical and chemical properties			
Physical state	Paste	PH	
Form	Cartridge	Log P octanol/water	Not stated
Colour	Grey/White/Black	Solubility in water	No reaction
Temperatures		Viscosity	-
Melting point		Vapour pressure	<110Kpa
Boiling point	-	Vapour density	-
Flash point	>55°C	Density	1.15 @1.19g/ml
Auto-ignition	-	Conductivity	
Explosion range	-	Odour	Solvents
Explosion range	-	VOC content	7 to 8% weight

10.

Stability and reactivity	
Conditions to avoid	
Materials to avoid	Oxidizing agent, strongly alkaline acid materials
Hazardous decomposition products	During polymerisation: CO₂, which in closed containers can result in pressurisation. In case of fire isocyanates, carbon monoxide and dioxide, smoke, nitrogen oxides, hydrogen chloride, hydrogen cyanide, sulfur dioxide.

11.

Toxicological information	
LD/LC Values	Diphenylmethane 4,4' diisocyanate LD50 Oral rat (mg/kg) >15000 LD50 Dermal rabbit(mg/kg) LC50 Inhalation rat (mg/1/4h) 0.49
Inhalation	May cause acute irritation and sensitization of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL.
Skin	Prolonged or repeated contact with skin may strip natural oil from skin causing non-allergic dermatitis on contact and absorption through the epidermis.
Eyes	Splashes in the eyes may cause irritation and reversible damage
Ingestion	

12.

Ecological information
The preparation has been assessed following the conventional method of the Dangerous Preparations Directive (199/45/EC) and classified for ecotoxicological hazards accordingly. See chapters 2 and 15 for details. The product should not be allowed to enter the water courses.

13.

Disposal considerations	
Product	Dispose in a safe manner in accordance with local / national regulations This product must not be allowed to run into drains or waterways.
Packaging	As chemical waste Disposal Code 080409

14.

Transport information			
Special precautions			
Classifications			
Packing group	Exempted	UN-number	
Do not store near food	-	RID/ADR	
Sea contaminating	-	ICAD/IATA	
Shipping name	-	IMDG-code	

15.

Regulatory information	
EC-classification	
Contains	DIPHENYLMETHANE 4.4'DIISOCYANATE
Symbol	Xn Harmful – contains isocyanates – see information supplied by the manufacturer
R-phrase	42/43 – May cause sensitization by inhalation and by skin contact 52/53 - Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment
S-phrases	2 – keep out of reach of children 23 – do not breathe vapours 36/37 – Wear suitable protective clothing and gloves 45 – In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) 46 – if swallowed seek medical advice immediately and show this container or label 63 – In case of accident by inhalation remove casualty to fresh air and keep at rest

16.

Other information		
Creation date	01.05.09	Production Management
Replace sheet of	05.01.09	Phill Blowers
<p>The information in this Safety Data Sheet is required in accordance with 67/548/CE and 99/45/CE Professional Table : n°4bis, 62,84 Text of R-Statements listed in ingredient§2</p> <p>10 Flammable 20 Harmful by inhalation 36/37/38 Irritating to eyes, respiratory system and skin 41 Risk of serious damage to eye 42/43 May cause sensitization by inhalation and skin contact 51/53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment 65 Harmful may cause lung damage if swallowed 66 Repeated exposure may cause skin dryness or cracking</p> <p>This leaflet is for general guidance only and may contain inappropriate information under particular conditions. Samples will be provided on request to enable customers to satisfy themselves as to the suitability of the product for any specific purpose and to assess the product under their own working conditions.</p>		