

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.10.2021

Version 5

Revision: 04.10.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Polyester Primers

Product code:

PLQ04 Easy Sand Primer Grey

PLQ05 High Build Primer Cream

PLQ06 Foundation

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Sprayable polyester primers for plugs and patterns.

For industrial or professional use only

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Llewellyn Ryland Ltd

Haden Street, Birmingham B12 9DB, United Kingdom

Tel: +44 (0)121 440 2284

Fax: +44 (0)121 440 0281

Email: technical@llewellyn-ryland.co.uk

1.4 Emergency telephone number: Llewellyn Ryland Ltd, Tel: +44 (0)121 440 2284 (office hours only , 7am - 7pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2	H225	Highly flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Repr. 2	H361d	Suspected of damaging the unborn child.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 1	H372	Causes damage to the hearing organs through prolonged or repeated exposure.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

styrene

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours/spray.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.10.2021

Version 5

Revision: 04.10.2021

Trade name: Polyester Primers

- P264 Wash thoroughly after handling.
 P273 Avoid release to the environment.
 P280 Wear protective gloves, protective clothing, eye protection/face protection.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

Additional information:

EUH208 Contains cobalt(II) 2-ethylhexanoate. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards Vapours may form ignitable mixture with air.**Results of PBT and vPvB assessment**

This mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Description:** Mixture of substances listed below with non-hazardous additions.**Dangerous components:**

CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.No.: 01-2119457861-32	styrene Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	25 - 50%
CAS: 7727-43-7 EINECS: 231-784-4 Reg.No.: 01-2119491274-35	barium sulfate substance with a Community workplace exposure limit	10 - 25%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.No.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	2.5 - 10%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide substance with a Community workplace exposure limit	2.5 - 10%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.No.: 01-2119471330-49	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	2.5 - 10%
CAS: 2457-01-4 EINECS: 219-535-8 Reg.No.: 01-2119983179-22	barium 2-ethylhexanoate Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332	≤ 2.5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.No.: 01-2119524678-29	cobalt(II) 2-ethylhexanoate Repr. 1A, H360Fd; Aquatic Acute 1, H400; Eye Irrit. 2, H319; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	≤ 2.5%

Additional information:

Titanium dioxide (CAS 13463-67-7): based on testing, this substance is not subject to the labelling requirements of Regulation (EU) 2020/217 (14th ATP of CLP).

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

In case of accident or if you feel unwell seek medical advice immediately (show label or SDS where possible).

In case of unconsciousness place patient stably in side position for transportation.



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.10.2021

Version 5

Revision: 04.10.2021

Trade name: Polyester Primers

After inhalation:

Remove person to fresh air and keep comfortable for breathing.
Seek medical treatment in case of complaints.
If respiratory activity is irregular or cessation of breathing appears give artificial respiration.

After skin contact:

Remove contaminated clothes immediately, wash the affected skin thoroughly with plenty of water.
In case of irritation seek medical treatment.
Wash contaminated clothes before reuse.

After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If irritation persists, get medical advice/attention.

After swallowing:

Rinse out mouth with water. Do NOT induce vomiting. Seek medical advice and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, dry chemical powder, foam or water spray
For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.
Formation of flammable or explosive air/vapour mixtures are possible.

5.3 Advice for firefighters**Protective equipment:**

In the case of fire wear self-contained respiratory equipment and protective suit.
Do not inhale explosion gases or combustion gases.

Additional information

Evacuate area and remove all ignition sources.
Cool endangered receptacles with water spray. Contain runoff to prevent entry into water or drainage systems.
Dispose of fire debris and contaminated fire fighting water according to the regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Please notice instructions for person-related safety precautions, wear protective equipment (see 8.)
Keep people at a distance and stay on the windward side.
Ensure adequate ventilation.
Turn leaking containers leak-side up to prevent the escape of liquid.
Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers, surface or ground water.
Contain the spilled material by bunding.
Do not allow product to enter sewage system or any watercourse.

6.3 Methods and material for containment and cleaning up:

Absorb with non-combustible absorbent material, (eg sand, diatomite, vermiculite).
Place into suitable and labelled containers for disposal.
Clean contaminated floors and objects thoroughly, observing environmental regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.10.2021

Version 5

Revision: 04.10.2021

Trade name: Polyester Primers

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent formation of aerosols.
Avoid any contact with skin, eyes and clothes.
Use only outdoors or in a well-ventilated area.
Do not eat, drink or smoke when using this product.
Wash hands before break and at the end of work.

Information about fire - and explosion protection:

Keep away from heat, sparks, open flames and hot surfaces. No smoking.
Protect against electrostatic charges.
Use explosion-proof apparatus / fittings and spark-proof tools.
Ground and bond container and receiving equipment.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Store in tightly closed containers in a cool and well ventilated place.
Protect from heat and direct sun.

Information about storage in one common storage facility:

Do not store food, beverages and animal feeding stuffs in the storage area.
Store away from strong acids or strong oxidising agents.

Further information about storage conditions:

Keep container tightly sealed.
Store in a place which is accessible only to authorised persons.

7.3 Specific end use(s) Use only according to instructions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 100-42-5 styrene

WEL Short-term value: 1080 mg/m³, 250 ppm; Long-term value: 430 mg/m³, 100 ppm

CAS: 7727-43-7 barium sulfate

WEL Long-term value: 10* 4** mg/m³; *inhalable dust **respirable dust

CAS: 141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm; Long-term value: 734 mg/m³, 200 ppm

CAS: 13463-67-7 titanium dioxide

WEL Long-term value: 10* 4** mg/m³; *total inhalable **respirable

CAS: 67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm; Long-term value: 1210 mg/m³, 500 ppm

Regulatory information WEL: EH40/2020

DNELs:

styrene (CAS 100-42-5):
workers, DNEL, acute effects systemic, inhalation 289 mg/m³
workers, DNEL, acute effects local, inhalation 306 mg/m³
workers, DNEL, chronic effects systemic, inhalation 85 mg/m³
workers, DNEL, chronic effects systemic, dermal 406 mg/kg bw/day
consumers, DNEL, acute effects systemic, inhalation 174.25 mg/m³
consumers, DNEL, acute effects local, inhalation 182.75 mg/m³
consumers, DNEL, chronic effects systemic, dermal 343 mg/kg bw/day
consumers, DNEL, chronic effects systemic, oral 2.1 mg/kg bw/day
consumers, DNEL, chronic effects systemic, inhalation 10.2 mg/m³

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.10.2021

Version 5

Revision: 04.10.2021

Trade name: Polyester Primers

ethyl acetate (CAS 141-78-6):

worker, DNEL, short-term exposure – systemic and local effects, inhalation 1468 mg/m³worker, DNEL, long-term exposure – systemic and local effects, inhalation 734 mg/m³

worker, DNEL, long-term exposure - systemic effects, dermal 63 mg/kg bw/day

consumer, DNEL, short-term exposure - systemic and local effects, inhalation 734 mg/m³

consumer, DNEL, long-term exposure - systemic effects, dermal 37 mg/kg bw/day

consumer, DNEL, long-term exposure - systemic effects, oral 4.5 mg/kg bw/day

consumer, DNEL, long-term exposure – systemic and local effects, inhalation 367 mg/m³

titanium dioxide (CAS 13463-67-7):

workers, DNEL, chronic effects local, inhalation 10 mg/m³

consumers, DNEL, chronic effects systemic, oral 700 mg/kg bw/day

PNECs:

styrene (CAS 100-42-5):

freshwater 0.028 mg/l, marine water 0.014 mg/l

sediment freshwater 0.614 mg/kg, marine water 0.307 mg/kg

intermittent releases 0.4 mg/l; STP 5 mg/l; soil 0.2 mg/kg

ethyl acetate (CAS 141-78-6):

freshwater 0.24 mg/l, marine water 0.024 mg/l

sediment freshwater 1.15 mg/kg, marine water 0.115 mg/kg

intermittent releases 1.65 mg/l; STP 650 mg/l; soil 0.148 mg/kg

titanium dioxide (CAS 13463-67-7):

freshwater 0.184 mg/l, marine water 0.0184 mg/l

sediment freshwater 1000 mg/kg, marine water 100 mg/kg

STP 100 mg/l; soil 100 mg/kg

8.2 Exposure controls**Appropriate engineering controls** Provide sufficient ventilation, particularly in closed areas.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

Avoid unnecessary contact with the product. Do not eat, drink or smoke at workplace.

Remove contaminated clothing immediately and wash carefully before reuse.

Do not breathe gas/vapours/spray.

Ensure that washing facilities are available at the work place.

Be sure to clean skin thoroughly after work and before breaks.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Chemical resistant gloves

Wash when contaminated. Dispose of when contaminated inside, when perforated or when contamination outside cannot be removed.

Material of gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Tightly sealed goggles (EN 166)

Ensure eye bath is to hand.

Body protection:

Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.10.2021

Version 5

Revision: 04.10.2021

Trade name: Polyester Primers

Environmental exposure controls

Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Fluid
Form:	Viscous liquid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available.
Lower and upper explosion limit:	No data available.
Flash point:	-2 - +0.5 °C
Auto-ignition temperature:	No data available.
pH:	5
Viscosity	
dynamic at 25 °C:	350,000 - 650,000 mPas (Brookfield RV 3)
kinematic:	Not determined.
Solubility	
water:	No data available.
Partition coefficient, n-octanol/water:	No data available.
Vapour pressure:	No data available.
Vapour density:	No data available.
Density:	No data available.

9.2 Other information

Explosive properties:	Not explosive.
Oxidising properties:	No data available.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity Stable under recommended transport or storage conditions.

10.2 Chemical stability Stable at ambient temperature and under normal conditions of use.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.10.2021

Version 5

Revision: 04.10.2021

Trade name: Polyester Primers

10.3 Possibility of hazardous reactions Vapours may form ignitable mixture with air.

10.4 Conditions to avoid Keep away from heat, sparks, open flames and hot surfaces.

10.5 Incompatible materials: Strong bases, strong acids and strong oxidising agents

10.6 Hazardous decomposition products:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

There are no product specific data on toxicology available.

CAS: 100-42-5 styrene

oral	LD50	> 2,000 mg/kg (rat)
dermal	LD50	> 2,000 mg/kg (rat) (OECD 402)
inhalative	LC50/4h	11.8 mg/l (rat)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Suspected of damaging the unborn child.

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure Causes damage to the hearing organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

For the product there are no ecotoxicological data available.

CAS: 100-42-5 styrene

LC50/96h	4.02 mg/l (flathead minnow, Pimephales promelas)
EC50/48h	4.7 mg/l (water flea, Daphnia magna)
ErC50/72h	4.9 mg/l (alga, Selenastrum capricornutum)
NOEC/21d	1.01 mg/l (water flea, Daphnia magna)

12.2 Persistence and degradability Styrene: easily biodegradable

12.3 Bioaccumulative potential

Styrene: BCF <100, octanol-water partition coefficient log Pow: 2.96 (25 °C)

Titanium dioxide: not bioaccumulating; BCF: 19-352 (Oncorhynchus mykiss)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects No further relevant information available.



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.10.2021

Version 5

Revision: 04.10.2021

Trade name: Polyester Primers

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Recommendation Transfer to a suitable container and arrange for collection by specialised disposal company.

Uncleaned packaging**Recommendation:**

Disposal must be made according to official regulations.

Not completely emptied packaging is to be disposed of in the same manner as the product.

SECTION 14: Transport information

14.1 UN number or ID number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
14.3 Transport hazard class(es) ADR Class Label IMDG, IATA Class Label	3 (F1) Flammable liquids. 3 3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Flammable liquids. 33
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso category P5c FLAMMABLE LIQUIDS

National regulations: -

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.10.2021

Version 5

Revision: 04.10.2021

Trade name: Polyester Primers

H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H360Fd May damage fertility. Suspected of damaging the unborn child.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further information:

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008:
Calculation method

Date of previous version: 28.06.2021**Abbreviations and acronyms:**

VLEP: Valeurs limites d'exposition professionnelle
CLP: REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CAS: Chemical Abstracts Service (division of the American Chemical Society)
EINECS: European Inventory of Existing Commercial Chemical Substances
WEL: workplace exposure limit
DNEL: Derived No-Effect Level
PNEC: Predicted No-Effect Concentration
EC50: maximal effective concentration, 50%
ErC50: median effective concentration for growth rate (algae)
LC50: lethal concentration, 50%
LD50: lethal dose, 50%
NOEL/NOEC: No Observed Effect Concentration
OECD: Organisation for Economic Co-operation and Development
BCF: bioconcentration factor
PBT: persistent, bioaccumulative and toxic properties
vPvB: very persistent and very bioaccumulative properties
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA: International Air Transport Association
IMDG: International Maritime Code for Dangerous Goods
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1A: Skin sensitisation – Category 1A
Repr. 1A: Reproductive toxicity – Category 1A
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Data compared to the previous version altered: Section 3
