

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : C134S Slow RTV Catalyst Green  
Product code : VRTSGC

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Main use category : Professional use, Industrial use  
Use of the substance/mixture : molding

#### 1.3. Details of the supplier of the safety data sheet

CFSNET Ltd  
United Downs Industrial Park  
St Day, Redruth  
Cornwall  
TR16 5HY  
T: +44 (0) 1209 821028  
sales@cfsnet.co.uk www.cfsnet.co.uk

#### 1.4. Emergency telephone number

Emergency number : +44 (0) 1209 821028  
Office hours only (08:30 - 16:45)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226  
Acute toxicity (inhalation:dust,mist) Category 4 H332  
Serious eye damage/eye irritation, Category 2 H319  
Skin sensitisation, Category 1 H317  
Reproductive toxicity, Category 2 H361d  
Specific target organ toxicity – Single exposure, Category 3, H335  
Respiratory tract irritation  
Specific target organ toxicity – Repeated exposure, Category 2 H373  
Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. May cause respiratory irritation. May cause an allergic skin reaction. Causes serious eye irritation.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Warning  
Contains : tetraethyl silicate; ethyl silicate; Dimethyltinneodecanoate  
Hazard statements (CLP) : H226 - Flammable liquid and vapour.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.

# C134S Slow RTV Catalyst Green

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP)	H332 - Harmful if inhaled.
	H335 - May cause respiratory irritation.
	H361d - Suspected of damaging the unborn child.
	H373 - May cause damage to organs through prolonged or repeated exposure.
	: P201 - Obtain special instructions before use.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
	P280 - Wear protective gloves, protective clothing, eye protection.
	P308+P313 - IF exposed or concerned: Get medical advice/attention.
	P321 - Specific treatment (see supplemental first aid instruction on this label).

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
tetraethyl silicate; ethyl silicate substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 78-10-4 EC-No.: 201-083-8 EC Index-No.: 014-005-00-0 REACH-no: 01-2119496195-28	$\geq 50$	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 STOT SE 3, H335
Dimethyltinneodecanoate substance with national workplace exposure limit(s) (GB)	CAS-No.: 68928-76-7 EC-No.: 273-028-6 REACH-no: 01-2120770324-57	1 – 25	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 2, H361d STOT RE 1, H372 Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

# C134S Slow RTV Catalyst Green

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.  
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

# C134S Slow RTV Catalyst Green

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### National occupational exposure and biological limit values

tetraethyl silicate; ethyl silicate (78-10-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Tetraethyl orthosilicate
IOEL TWA	5 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
United Kingdom - Occupational Exposure Limits	
Local name	Tetraethyl orthosilicate
WEL TWA (OEL TWA)	44 mg/m <sup>3</sup>
	5 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Dimethyltinneodecanoate (68928-76-7)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	0.1 mg/m <sup>3</sup>

### 8.2. Exposure controls

#### Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Personal protection equipment

##### Personal protective equipment symbol(s):



#### Eye and face protection

##### Eye protection:

Safety glasses

#### Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

#### Respiratory protection

##### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

# C134S Slow RTV Catalyst Green

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Green.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Flammable liquid and vapour.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 23 – 60 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 20 mPa·s (25°C)
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0.93 – 0.98 g/cm <sup>3</sup> (25°C)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# C134S Slow RTV Catalyst Green

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

##### Catalyst C134S Green

ATE CLP (dust,mist)	1.697 mg/l/4h
---------------------	---------------

##### tetraethyl silicate; ethyl silicate (78-10-4)

LD50 oral rat	> 2500 mg/kg Source: ECHA
---------------	---------------------------

LD50 dermal rabbit	> 2000 mg/kg Source: ECHA
--------------------	---------------------------

LC50 Inhalation - Rat (Dust/Mist)	10 mg/l Source: ECHA
-----------------------------------	----------------------

##### Dimethyltinneodecanoate (68928-76-7)

LD50 oral rat	892 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 690 - 1160
---------------	---

LD50 dermal rabbit	> 2000 mg/kg
--------------------	--------------

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Suspected of damaging the unborn child.  
STOT-single exposure : May cause respiratory irritation.

##### tetraethyl silicate; ethyl silicate (78-10-4)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

##### Dimethyltinneodecanoate (68928-76-7)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard : Not classified

##### tetraethyl silicate; ethyl silicate (78-10-4)

Viscosity, kinematic	0.798 mm²/s
----------------------	-------------

#### 11.2. Information on other hazards

No additional information available

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

##### tetraethyl silicate; ethyl silicate (78-10-4)

LC50 - Fish [1]	> 245 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
-----------------	---

# C134S Slow RTV Catalyst Green

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Dimethyltinneodecanoate (68928-76-7)

EC50 - Crustacea [1]	39 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	16 mg/l

### 12.2. Persistence and degradability

#### Catalyst C134S Green

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### tetraethyl silicate; ethyl silicate (78-10-4)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### Dimethyltinneodecanoate (68928-76-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

### 12.3. Bioaccumulative potential

#### tetraethyl silicate; ethyl silicate (78-10-4)

Partition coefficient n-octanol/water (Log Pow)	0.04 Source: ChemIDplus
---	-------------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.

# C134S Slow RTV Catalyst Green

## Safety Data Sheet






according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HP Code

: HP3 - "Flammable:"  
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;  
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;  
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;  
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;  
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;  
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.  
HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.  
HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.  
HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1993	UN 1993	UN 1993	UN 1993	UN 1993
<b>14.2. UN proper shipping name</b>				
FLAMMABLE LIQUID, N.O.S. (CONTAINS : tetraethyl silicate; ethyl silicate)	FLAMMABLE LIQUID, N.O.S. (CONTAINS : tetraethyl silicate; ethyl silicate)	Flammable liquid, n.o.s. (CONTAINS : tetraethyl silicate; ethyl silicate)	FLAMMABLE LIQUID, N.O.S. (CONTAINS : tetraethyl silicate; ethyl silicate)	FLAMMABLE LIQUID, N.O.S. (CONTAINS : tetraethyl silicate; ethyl silicate)
<b>Transport document description</b>				
UN 1993 FLAMMABLE LIQUID, N.O.S. (CONTAINS : tetraethyl silicate; ethyl silicate), 3, III, (D/E)	UN 1993 FLAMMABLE LIQUID, N.O.S. (CONTAINS : tetraethyl silicate; ethyl silicate), 3, III	UN 1993 Flammable liquid, n.o.s. (CONTAINS : tetraethyl silicate; ethyl silicate), 3, III	UN 1993 FLAMMABLE LIQUID, N.O.S. (CONTAINS : tetraethyl silicate; ethyl silicate), 3, III	UN 1993 FLAMMABLE LIQUID, N.O.S. (CONTAINS : tetraethyl silicate; ethyl silicate), 3, III
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
III	III	III	III	III
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-E EmS-No. (Spillage): S-E	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No



# C134S Slow RTV Catalyst Green

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3Y

#### Transport by sea

Special provisions (IMDG)	: 223, 274, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
Stowage category (IMDG)	: A

#### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

#### Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 274, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

#### Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 274, 601

# C134S Slow RTV Catalyst Green

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road

# C134S Slow RTV Catalyst Green

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2

# C134S Slow RTV Catalyst Green

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.