

Z999 General Purpose Resin

Product type

Unsaturated polyester resin in styrene, special

Appearance

Main resin characteristics Preaccelerated Thixotropic

Main applications General purpose

Moulding informations Hand lay up and Spray up

Technical data sheet

First Emission: 04/05/2020

Version: 1, 13/03/2023

Shelf life and storage

Store in the shade, out of direct sunlight. Keep storage temperature below 25°C. Unseal container just before use. Shelf-life will be reduced reaching higher temperature.

Precaution for handling

Read carefully the Safety Data Sheet Stir the resin before use, without introducing air

FEATURES OF THE LIQUID RESIN (1) Properties	Test Method	<u>Unit</u>	Typical values
Specific weight at 25°C		g/cm³	1.11
Brookfield LVT at 25ºC, sp 2 rpm 12	A040	mPa.s	600-2000
Cone & Plate		mPa.s	100-600
	at 25°C + 1% MEKP50		
Gel time (2)	G020	minutes	20-50
Acid value	K060	mgKOH/g	< 30
Storage stability at 23°C in the dark	MT-CU 002S	months	3

Thoroughly test in your applications before full-scale use. Geltimes may vary due to the reactive nature of these materials and due to different brands of curing additives. Always test on small scale before formulating large quantities.

2) If present cobalt is herewith intended as octoate. Use of different Cobalt salts could result in different geltimes. Always test on small scale before formulating large quantities.

PROPERTIES OF THE CURED UNREINFORCED RESIN (3)

3) Properties are typical values, based on material tested in our laboratories, but varies from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

The information contained in this document (which is to be intended only for explanatory purposes) is correct and accurate and is based on our technical and scientific knowledge and on literature at the date of publication. Such information relates only to use of the products in the pure state and for the purposes stated herein. Nothing in the information contained in this document shall be deemed to be a warranty or a representation (explicit or implicit) by the manufacturer, and/or taken or construed as infringing of any existing patents. The manufacturer shall not be under any liability or responsibility for any of the information provided under this document or for any errors, omissions or misstatements, even with regard to results to be obtained through the use of the aforesaid information.